



ΙΑΤΡΙΚΟΣ ΕΞΟΠΛΙΣΜΟΣ
ΑΝΑΛΩΣΙΜΑ

ΕΞΕΤΑΣΤΙΚΟΙ
ΦΑΚΟΙ &
ΦΩΤΙΣΜΟΣ



MEGA

5-dioptre LED magnifying lamp of cold light. It is equipped with an articulated arm and a clamp to fix it on tables or beauty trolleys and with a very stable 5-wheel compact base. Wall-mounted option also available.

Magnifying Lamp
Ref. WKL003

Input voltage: 220Vac-240Vac
Input frequency: 50Hz/60Hz
Power: 8 W
Dioptres: 5 dioptres
Luminous flux: 760 lumen
Type of led: SMD.LED - 60 pcs
AC Power cord size: 150 cm



Τιμή: Επικοινωνήστε μαζί μας

OPTIONS
Ref. 10063

PACKING SIZE
WKL003T
76x27x10 cm
N.W. kg
3.5
G.W. kg
4

WHEELS.3
55x43x14 cm
N.W. kg
9.5
G.W. kg
10.5



Ref. WHEELS.3 (Stand for WKL003 Lamp)

ZOOM

Modern LEDs lamp of cold light with a 5X magnification. The intensity of light can be adjusted. Its articulated arm eases the movement and lamp fixation safely. It comes with a high-stability 5-wheel base.



Τιμή: Επικοινωνήστε μαζί μας



- Led Magnifying Lamp
Ref. 1006

AMPLI

Modern LEDs lamp of cold light with 5X magnification. Its articulated arm eases the movement and lamp fixation safely. It comes with a high-stability 5-wheel base.



Τιμή: Επικοινωνήστε μαζί μας



- Led Magnifying Lamp
Ref. 1005

EXPAND

Lamp with cold fluorescent light with 3X magnification. Its articulated arm eases the movement. It comes with a high stability 5-wheel base.



Τιμή: Επικοινωνήστε μαζί μας



- Magnifying Lamp
Ref. 1001

THERAP

Infrared lamp with a 275W bulb for thermotherapy treatments. Its articulated arm eases the movement and fixes the lamp with total comfort. It comes with a high stability 5-wheel base.

Τιμή: Επικοινωνήστε μαζί μας



- Infrared Lamp
Ref. 1003

DIAGNOS

–
Wood Lamp
Ref. 1004

Ultraviolet light lamp for skin diagnose and analysis.



Τιμή: Επικοινωνήστε
μαζί μας



LUXIFLEX HALOGEN LIGHT - trolley

Technical Specifications

- Stainless steel chamber: \varnothing 24.5 x 40 cm (Plus)
- External size: 44 x 38 x 50 cm (W x H x D)
- Net weight: 35 kg
- 2 sterilization cycles: 121°C and 134°C
- Operating Voltage: 230V \pm 10% - 50/60Hz
- Power consumption: 1700 W
- Class N
- Made in Italy - Warranty: 1 year

- Cycle: Not wrapped 121° C

• Materials:

- Fragile solids
- Rubber solids
- Glass
- Turbines (if indicated by producer)

- Sterilization time: 20 min

- Drying time: 5 min

- Max load: 2.8 kg (700 g load in any tray)

- Working pressure: 1.2 - 1.3 bars

- Cycle: Not wrapped 134° C

• Materials:

- Stainless metal solids
- Turbines (if indicated by producer)

- Sterilization time: 10 min

- Drying time: 5 min

- Max load: 2.8 kg (700 g load in any tray)

- Working pressure: 2.1 - 2.2 bar

Τιμή: Επικοινωνήστε
μαζί μας



LUXIFLEX HALOGEN LIGHT

Technical Specifications

- Stainless steel chamber: \varnothing 24.5 x 40 cm (Plus)
- External size: 44 x 38 x 50 cm (W x H x D)
- Net weight: 35 kg
- 2 sterilization cycles: 121°C and 134°C
- Operating Voltage: 230V \pm 10% - 50/60Hz
- Power consumption: 1700 W
- Class N
- Made in Italy - Warranty: 1 year

- Cycle: Not wrapped 121° C
- Materials:
 - Fragile solids
 - Rubber solids
 - Glass
 - Turbines (if indicated by producer)
- Sterilization time: 20 min
- Drying time: 5 min
- Max load: 2.8 kg (700 g load in any tray)
- Working pressure: 1.2 - 1.3 bars

- Cycle: Not wrapped 134° C
- Materials:
 - Stainless metal solids
 - Turbines (if indicated by producer)
- Sterilization time: 10 min
- Drying time: 5 min
- Max load: 2.8 kg (700 g load in any tray)
- Working pressure: 2.1 - 2.2 bar

Τιμή: Επικοινωνήστε μαζί μας



LUXIFLEX LED LIGHT

Technical Specifications

- Type of lighting: LED
- Consumption: 10W
- Life of the bulbs: 25000 h
- Light intensity at 50 cm: 15000 lux
- Colour temperature \pm 5% at 1 m: 3000 K
- Colour: white
- Norms: EN 60601-1-2
- Marks: CE 93/42
- Weight: 9 kg
- Operating voltage: 230 V - 50Hz
- Operating voltage (on request): 110 V - 50/60 Hz

Τιμή: Επικοινωνήστε μαζί μας



MINIMED HALOGEN LIGHT

Technical Specifications

- Type of lighting: halogen
- Consumption: 50W
- Light intensity at 50 cm: 38000 lux
- Colour temperature $\pm 5\%$ at 1 m: 3100 K
- Colour: white
- Norms: IEC 60601-1
- Marks: CE 93/42
- Weight: 9 kg
- Operating voltage: 230 V - 50/60W

Τιμή: Επικοινωνήστε μαζί μας



MINIMED LED LIGHT

Technical Specifications

- Type of lighting: LED
- Consumption: 12W (4 x 3)
- Light intensity at 50 cm: 20000 lux
- Colour temperature $\pm 5\%$ at 1 m: 6500 K
- Colour: white
- Norms: IEC 60601-1
- Marks: CE 93/42
- Weight: 9 kg
- Operating voltage: 230 V - 50/60W
- Operating voltage (on request): 110 V - 50/60 Hz

Τιμή: Επικοινωνήστε μαζί μας



SATURNO OPERATING LED LIGHT wall

Technical Specifications

- Light intensity at 1 m distance: 30,000 lux
- Colour temperature adjustable: 4500/5000 \pm 5% °K
- 9 LEDs: 2.5 W
- Average LED life: 50,000 h
- CRI (chromatic rendering Index): 96 Ra
- Light field where the illumination reaches 10% of Ec (d10): \varnothing 25 cm
- Light field where the illumination reaches 50% of Ec (d50): \varnothing 12.5 cm
- Depth of illumination IEC 60601-2-41 (L1+L2) at 20% of Ec: 228 cm
- Depth of illumination IEC 60601-2-41 (L1+L2) at 60% of Ec: 136 cm
- Total radiated energy Ec: 105 W/m²
- Diameter of the reflector: 19.5 cm
- Useful lighting surface of the cupola: 65 cm²
- Weight (ceiling, mobile, wall): 12 - 14 - 13 kg
- Power requirements: 100-240V, 50-60 Hz
- Minimum height of the room (ceiling version): 240 cm
- Standards: IEC 60601-1 IEC 60601-2-41, MDD 93/42 CEE, medical device of Class I
- Warranty 12 months - mechanical components warranty 10 years
- Made in Italy



Τιμή: Επικοινωνήστε μαζί μας

SATURNO OPERATING LED LIGHT ceiling

Technical Specifications

- Light intensity at 1 m distance: 30,000 lux
- Colour temperature adjustable: 4500/5000 \pm 5% °K
- 9 LEDs: 2.5 W
- Average LED life: 50,000 h
- CRI (chromatic rendering Index): 96 Ra
- Light field where the illumination reaches 10% of Ec (d10): \varnothing 25 cm
- Light field where the illumination reaches 50% of Ec (d50): \varnothing 12.5 cm
- Depth of illumination IEC 60601-2-41 (L1+L2) at 20% of Ec: 228 cm
- Depth of illumination IEC 60601-2-41 (L1+L2) at 60% of Ec: 136 cm
- Total radiated energy Ec: 105 W/m²
- Diameter of the reflector: 19.5 cm
- Useful lighting surface of the cupola: 65 cm²
- Weight (ceiling, mobile, wall): 12 - 14 - 13 kg
- Power requirements: 100-240V, 50-60 Hz
- Minimum height of the room (ceiling version): 240 cm
- Standards: IEC 60601-1 IEC 60601-2-41, MDD 93/42 CEE, medical device of Class I
- Warranty 12 months - mechanical components warranty 10 years
- Made in Italy



Τιμή: Επικοινωνήστε μαζί μας

Mach LED 115

Technical Specifications

Brightness / 0.5 meters (Lux): 60,000
CRI: 95
Color temperature (K): 4000
Dimming range (%): 50-100
Number of LEDs: 7
Focusable light field size (cm): 14 (fixed focus)
Total Power (W): 10
Durability of the lamp (h): $\geq 40,000$



Τοίχου - οροφής - τροχύλατο

Τιμή: Επικοινωνήστε μαζί μας

Mach LED 130

Technical Specifications

Brightness / 1 meter (Lux): 60,000
CRI: 95
Color temperature (K): 4300
Dimming range (%): 50-100
Number of LEDs: 19
Focusable light field size (cm): 17 (fixed focus)
Total Power (W): 28
Durability of the lamp (h): $\geq 40,000$
Workspace (cm): 70-140



Τοίχου - οροφής τροχύλατο

Τιμή: Επικοινωνήστε μαζί μας

LED 2 MC



Technical Specifications

Brightness / 1 meter (Lux): 115,000

CRI: ≥ 96

Color temperature (K): 3750, 4000, 4250, 4500, 4750

Dimming range (%): 5-100

Number of LEDs: 84

Focusable light field size (cm): 17-28

Total Power (W): 70

Durability of the lamp (h): $\geq 40,000$

Workspace (cm): 60-150

Τιμή: Επικοινωνήστε
μαζί μας



Αισχύλου 83, Νίκαια

Τηλ.: 211 4112707 - 6939 080534, 6931 981515

E-mail: info@sfaid.gr - Site: www.sfaid.gr